



### Concrete Prove Soft Decore

**DESCRIPTION** This product is a high quality water-based paint. It is made of strong acrylic copolymer and contains solid aggregates of coarse rocks.

**Features and benefits** It has a unique look that is inspired by the famous limestone. It contains coarse aggregate to add a luxurious stone appearance. Its original stone texture makes it the ideal coating for modern or traditional homes.

**Recommended use** Ideal for decoration of exterior surfaces.

**Substrate** Cement plaster, concrete, block work, rendered surfaces etc.  
Substrate should have sufficient strength to receive the paint. Any defects in the substrate like surface undulations, cracks, pin holes etc.

#### Properties

<b>colors</b>	White
<b>Solids ( % volume)</b>	57 ± 2
<b>Specific gravity</b>	1.75 gm/cm <sup>2</sup>
<b>Dilution</b>	Maximum 10 %
<b>thinner</b>	water
<b>tools</b>	Spatula, Trowel (Made of stainless steel).

**Conditions during application** The temperature of the substrate should be minimum 10 °C and at least 3 °C above the dew point of the air, measured in the vicinity of the substrate. The ideal maximum substrate temperature during application should not be more than 45 °C. Good ventilation is usually required in confined areas to ensure proper drying.  
Do not apply when ambient temperature is below 5 degrees or higher than 40 degrees.  
Do not apply in direct sunlight around noon in hot summer month.  
Do not apply during rainfall. Keep well away from rainfall and other water sources until paint is fully dry.  
Do not apply on Surfaces that are subject to water leakage.





## Concrete Prove Soft Decore

Drying times	Relative Humidity (RH) 50 %		
	10 °C	23 °C	23 °C
Substrate temperature	10 °C	23 °C	23 °C
Hard dry	24	5	3
Dry to over coat, minimum	24	5	3

### Surface preparation

The substrate must be sound, clean, dry and free from dust, oil, grease, laitance etc. All traces of form release agents/curing agents must be removed. A light sanding with suitable abrasive material is recommended before application. Any resulting dust/loose particles must be removed.

### Recommended paint system

product	No.of coats
Concerete selear Alkali	1
Concrete Prove Soft Decore	2

**size of the packages** - 10 L - 20 L.

### Storage

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

