



Concrete dry Sealer

Description

- A highly efficient water-based primer with acrylic based on a special acrylic base.
- This primer has been specially prepared to achieve good penetration inside the surface and it is considered one of the best types of primers for internal surfaces.

Uses

- Very suitable for gypsum, concrete and fiberglass concrete surfaces.
- It is important to apply Dry Sealer concrete to all places where weather resistance and good penetration is required.

Characteristics

- Good penetration of concrete and plaster gives good adhesion to the following layers.
- It provides high resistance to alkali present in new cement surfaces.

Usage data

- Application methods: Roller brush, anaerobic or conventional spray.
- Diluted: With 5% water as a maximum.

Conditions During Use

- The surface temperature should not be less than 10 ° C as a minimum, and the surface temperature should be at least 3 ° C higher than the dew point.

Drying time: at least an hour, knowing that high moisture delays the drying process.

Technical Data

Basis	It has a special acrylic base that is resistant to alkali.
color	white
Density	1.25 – 1.35 gm/cm ³
Solid content	25 ± 2 (According to the percentage of size)

Packaging

Dry Sealer is available in 10 liter and 20 liter containers.

Coverage

- 9 to 12 m² / l. The coverage rate may vary depending on the surface condition.



Concrete dry Sealer

thickness of the paint layer

- Dry: 28 - 34 (μm).
- Non-dry: 110-140 (μm).

Surface preparation

- The surfaces must be clean, dry and thoroughly treated, and they must be completely free of dust and suspended matter.
- Surfaces must be sanded and then cleaned before painting in order to get the best results.

Product application

- Apply Dry Sealer using a brush or roller or by spraying on the surface to be sealed.
- The first layer must be left to dry for at least 2-4 hours.

Storage

- Shelf life is 24 months from manufacturing date, in original sealed containers away from direct sunlight, and in a dry, covered storage area.

Handling

- Carefully, and stir well before use.

Health and Safety

- While using the product, gloves and goggles should be worn.
 - Splashes to skin or eyes should be washed with clean water.
-

