



## Concrete Rubber Matt 5000

**DESCRIPTION** an acrylic copolymer based emulsion paint with outstanding washability it has a good flow and gives a smooth flat finish.

**Features and benefits** Offers a smooth semi-flat finish.  
Easy to apply and good spreading; high covering and retouching properties. No splash during application; no brush or roller marks. Odourless paint, no odour during and after paint application.

**Uses** Ideal for interior surfaces .

### Properties \_

<b>colors</b>	White + tinted on the multicolor machine	
<b>Solids ( % volume)</b>	35 ± 2	
<b>Specific gravity</b>	1.48 gm/cm <sup>2</sup>	
<b>viscosity</b>	108 K.U.	
<b>Film thickness per coat</b>	Dry	Wet
	45 - 60 µm	125 - 170 µm
<b>thinner</b>	water	
<b>Dilution</b>	Maximum 20 %	
<b>tools</b>	Airless spray, brush, roller or conventional spray	

### Guiding data airless spray

pressure at nozzle	150 kp/cm <sup>2</sup>
nozzle tip	0.021 – 0.027 inch
spray angle	65° - 80°

**Conditions during application** The temperature of the substrate should be minimum 10 °C and at least 3 °C above the dew point of the air, measured in the vicinity of the substrate

<b>Drying times</b>			
Substrate temperature	23 °C	35 °C	45 °C
Surface (touch) dry	6 h	4 h	2 h
Hard dry	8 h	6 h	4 h

### Surface preparation

If the surface needs to be prepared before painting, rubber primer, rock 2000

**Packsize** 10 L , 20L .

**Storage** The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

	product	NO.of coats
On plaster or concrete surfaces	Rubber p	1
	Rock 2000	2
	C.R.Matt	2
On gypsum plaster or chalky s	Penetrating sealer	1
	Rock 2000	2
	C.R.Matt	2

